

RXW104

Power Handling
250 Watts RMS / 500 Watts Max.

Single Voice Coil
Subwoofer 25 cm

Recommended Enclosure

Sealed Box
 Sealed Volume: 15 - 30 L

Compact

Recommended Enclosure

Ported Box
 Vented Volume: 19 L
 Port Diameter: 76 mm
 Port Area: 45 cm²
 Port Length: 22 cm
 Tuning Freq. (Fb): 49 Hz
 -3 dB Rolloff (F3): 45 Hz

Deep Tuning

Technical Specifications

Impedance	Zn	4 Ohms
Voice Coil Diameter	Ø	50 mm
Voice Coil Winding Height		19 mm
Max. Linear Excursion	Xmax	+/- 6,5 mm
Max. Mechanical Excursion	Xmax (Peak)	+/- 13 mm
Cone Area	Sd	340 cm ²
Moving Mass	Mms	88,1 g
DC Resistance	Re	3,2 Ohms
Resonance Frequency	Fs	35 Hz
Mechanical Q-Factor	Qms	6,9
Electrical Q-Factor	Qes	0,72
Total Q-Factor	Qts	0,65
Equivalent Air Volume	VAS	38 L
VC Inductance	Le	1,69 mH
Flux Density	B/L	9,5 N/A
Efficiency 1W/1m	SPL	86 dB

Mechanical Components

- Steel Basket
- Polypropylene Cone
- Foam Surround
- Injected PP Dustcap
- Single Spider
- Y25 Magnet 24 oz (680 g)
- Magnet Size: Ø110 x 20 mm
- Kapton Voice Coil Former

Dimensions & Weight

External Diameter: 254 mm
 Mounting Diameter: 228 mm
 Mounting Depth: 107 mm
 Shipping Weight: 3,2 kg

